

# 投射 / 光學用MR16 - 50mm 鹵鎢燈 (GZ6.35, GX5.3, GU5.3 燈腳)

## Projection / Optical MR16 - 50mm halogen lamp (GZ6.35, GX5.3, GU5.3 base)

日本製造  
Made in Japan

### 燈泡參數

#### PHYSICAL DATA AND CHARACTERISTICS

型號 Type	美式代碼 Ref. ANSI	電壓 Volts (V)	功率 Watts (W)	色溫 Colour Temp. (K)	每箱數量 Std. Pkg. Qty.	平均壽命 Rated Av. Life (hrs)	工作距離 Working Distance mm (in)	燈頭 Base	鹵鎢鎢絲 Filament	圖 Fig. No.
------------	-------------------	-----------------	--------------------	---------------------------	---------------------------	---------------------------------	----------------------------------------	------------	------------------	------------------

MR16 dichroic reflector JCR - GZ6.35, GX5.3, GU5.3 bases without cover glass



JCR12V20W20H/G1	—	12	20	2950	50	2000	32 (1.3)	GZ6.35	C-6	1
JCR12V30W20H/G1	—	12	30	3000	50	2000	32 (1.3)	GZ6.35	C-6	1
JCR6V50W20H/G1	—	6	50	3000	50	2000	50 (2)	GZ6.35	C-8	1
JCR12V50W20H/G1	—	12	50	3000	50	2000	32 (1.3)	GZ6.35	C-8	1
JCR12V50W20H/G1UV	—	12	50	3000	50	2000	32 (1.3)	GZ6.35	C-8	1
JCR9.5V55W15H/G1	—	9.5	55	3000	50	1500	—	GZ6.35	C-8	1
JCR12V75W/G1	EFN	12	75	3400	50	50	32 (1.3)	GZ6.35	C-8	1
JCR12V75W15H/G1	—	12	75	3000	50	1500	32 (1.3)	GZ6.35	C-8	1
JCR12V100W/G1	EFP	12	100	3400	50	50	32 (1.3)	GZ6.35	C-8	1
JCR12V100W10H/G1	—	12	100	3100	50	1000	32 (1.3)	GZ6.35	C-8	1
JCR15V150W/G1	EFR	15	150	3400	50	50	32 (1.3)	GZ6.35	C-8	1
JCR15V150W5H/G1	—	15	150	3200	50	500	32 (1.3)	GZ6.35	C-8	1
JCR24V150W10H/G2/H50	—	24	150	3200	50	1000	—	GX5.3	CC-6	2
JCR24V200W10H/G2/H50	—	24	200	3200	50	1000	—	GX5.3	CC-6	2
JR1505	EPZ	13.8	50	3150	12	1000	—	GX5.3	C-6	3

備註：任何角度的燃點位置。 Notes: Burning position: Any

### 鑽石紋反光杯 FACETED REFLECTOR




Fig.1




Fig.2




Fig.3